

COATING THICKNESS GAUGE CODE ISO-8000FN

SUITABLE FOR THIN COATING
BELOW 10μm

FOR MAGNETIC AND
NON-MAGNETIC SUBSTRATES



calibration foils (included)



zero calibration plate
(included)



stand (optional)



eddy current probe N2000
(optional)



eddy current probe N1500
(optional)



magnetic induction
probe F500
(included)

- Can measure thickness of thin coating below 10μm
- High repeatability
- Magnetic induction probe measures the thickness of non-magnetic coating and non-metallic coating on magnetic metal substrate
Substrate: iron, steel, magnetic stainless steel (not for non-magnetic stainless steel)
Coating: zinc, aluminum, copper, chrome, tin, plastic, powder, paint (not for nickel)
- Eddy current probe measures the thickness of non-conductive coating on non-magnetic metal substrate
Substrate: copper, aluminum, zinc, non-magnetic stainless steel
Coating: plastic, powder, paint, anodizing (not for chrome and zinc plating)
- Maximum, minimum, average and variance values can be calculated automatically

SPECIFICATION

Probe		F500 (included) magnetic induction probe	N1500 (optional) eddy current probe	N2000 (optional) eddy current probe
Measuring range		0~500μm	0~1500μm	0~2000μm
Resolution		0.1μm (range<100μm) 1μm (100μm≤range≤500μm)	0.1μm (range<100μm) 1μm (100μm≤range<1000μm) 0.01mm (range≥1.00mm)	0.1μm (range<100μm) 1μm (100μm≤range<1000μm) 0.01mm (range≥1.00mm)
Accuracy *		±(0.5μm+2%L)		
Repeatability *		≤(0.2μm+0.8%L)		≤(0.2μm+1%L)
Measuring mode		single and continuous		
Measure interval	single mode	1.5s	0.8s	
	continuous mode	0.4s	0.4s	
Calibration mode		zero calibration and multi-points calibration (1~5 points)		
Minimum substrate thickness		0.1mm	0.05mm	
Minimum measuring area		Ø7mm		Ø25 mm
Minimum radius of curvature workpieces	convex surface	1.5mm		
	concave surface	10mm		
Unit		μm/mil		
Power supply		4×1.5V AAA batteries		
Dimensions (L×W×H)		148×76×26mm		
Net weight		148g		

STANDARD DELIVERY

Main unit	1 pc
Magnetic induction probe (ISO-8000FN-F500)	1 pc
Zero calibration plate	1 pc
Calibration foils (5.6μm, 11.6μm, 24.6μm, 50.0μm, 100μm, 252μm, 390μm)	1 set
1.5V AAA battery	4 pcs

OPTIONAL ACCESSORY

Eddy current probe (with zero calibration plate and standard foil)	ISO-8000FN-N1500 **
Eddy current probe (with zero calibration plate and standard foil)	ISO-8000FN-N2000
Stand	ISO-8000FN-STAND

* L is measuring thickness in μm

** For precision measurement of thin coating below 10μm, please use the stand for eddy current probe