

VIDEOSCOPES (BASIC TYPE)

TUNGSTEN WIRE WEAVED CABLE BREAK AND WEAR RESISTANCE








WIFI real-time image transmission



replaceable lens cable





SPECIFICATION

Code		ISV-J2810	ISV-J2815	ISV-J4010	ISV-J4030	ISV-J6010	ISV-J6030	
Lens	diameter (ØD)	2.8mm	2.8mm	4.0mm	4.0mm	6.0mm	6.0mm	
	pixel	0.16M		1M				
	resolution	400×400	400×400		1280×720			
	depth of field	10~∞mm	10~∞mm					
	bending direction	four direction	four directions					
	bending range (α)	±160°	±160°					
	angle of view (θ)	120°	120°					
	illumination	front LED	front LED					
	lens	sapphire glas	sapphire glass lens					
	dust/waterproof	IP67	IP67					
	bend control	manual joyst	manual joystick					
Cable	length	1m	1.5m	1m	3m	1m	3m	
	type	wire weaved	wire weaved cable					
Main unit	display	5" HD screer	5" HD screen (resolution: 1920x1080)					
	function	take pictures	take pictures, take videos					
	file format	picture: JPG	picture: JPG, video: MOV					
	image process	image zoom	image zoom (1X, 2X, 3X, 4X, 5X)					
	image control	freeze, flip o	freeze, flip over, playback, analog ruler					
	memory	32G memory	32G memory card					
	output	WIFI (only fo	WIFI (only for Android OS), USB, HDMI					
	power supply		rechargeable lithium battery (working time ≥ 4 hours), AC/DC adapter (for continuous working)					
Weight		1000g	1000g					

STANDARD DELIVERY Main unit **OPERATION ENVIRONMENT** 1 pc 32G SD card Main unit -10~50°C, no preheat 1 pc Card reader Operation temperature -20~70°C 1 pc -20~60°C USB cable Storage temperature 1 pc

Relative humidity

1 pc

maximum 90%, no condensation

AC/Dc adapter